

ESPECIFICACIÓN DE PRODUCTOS



DUCTO ELÉCTRICO UL TIPO A -19'

SONACA 
Productos que resisten toda una vida

Tubos PVC	1/2"	3/4"	1"	1 1/4"
Norma:	NORDOM 855	NORDOM 855	NORDOM 855	NORDOM 855
Código:	3TA-0050	3TA-0075	3TA-0100	3TA-0125
Color:	Gris	Gris	Gris	Gris
Densidad.: (kg/mm³)	.00000142	.00000142	.00000142	.00000142
Dispersión.:	6%	6%	6%	6%
Ovalidad E/S.: (mm)	0.41	0.76	0.51	0.61
Espesor pared Min.: (mm)	1.52	1.52	1.52	1.78
Espesor pared Nom.: (mm)	1.57	1.57	1.57	1.84
Espesor pared Max.: (mm)	1.61	1.61	1.61	1.89
Longitud Min.: (mm)	5800	5800	5800	5800
Longitud Max.: (mm)	5820	5820	5820	5820
Ø interno Min. Exterior: (mm)	21.34	26.57	33.27	42.03
Ø interno Nom. Exterior: (mm)	21.39	26.67	33.40	42.16
Ø interno Max. Exterior: (mm)	21.44	26.77	33.53	42.29
Peso Min.: (Kg.)	0.78	0.99	1.25	1.85
Peso Nom.: (Kg.)	0.81	1.02	1.29	1.92
Peso Max.: (Kg.)	0.83	1.05	1.33	1.98
Empaque 1:(uds. x caja.)	25	25	25	10
Prueba de impacto (lb/ft):	30	40	80	120
Longitud de campana Min.:	16.56	31.75	38.10	44.45
Longitud de campana Max.:	16.56	31.75	38.10	44.45
Ovalamiento de Camp. Max.: (mm)	0.41	0.71	0.76	0.86
Ø Interno ent. Camp. Nom.: (mm)	21.44	26.87	33.65	42.42
Ø Interno ent. Camp. Min.: (mm)	21.64	26.77	33.52	42.29
Ø Interno ent. Camp. Max.: (mm)	21.84	26.97	33.78	42.55
Deflexión Bajo Carga (Rigidez):	120	300	300	300
Aplastamiento: (%)	70	70	70	70

Grabado:

Ø DE LA TUBERÍA RIGID PVC TYPE A UNDERGROUND ONLY-ENCASE IN CONCRETE PVC 1120 UL-651 (LOGO UL) / NORDOM 855 (sello) CORVI SONACA (LOGO CORVI) MADE IN DOMINICAN REPUBLIC /FECHA/HORA/MAQUINA NO. / HILERA NO.

ESPECIFICACIÓN DE PRODUCTOS



DUCTO ELÉCTRICO UL TIPO A -19'

SONACA 
Productos que resisten toda una vida

Tubos PVC	1 1/2"	2"	3"	4"
Norma:	NORDOM 855	NORDOM 855	NORDOM 855	NORDOM 855
Código:	3TA-0150	3TA-0200	3TA-0300	3TA-0400
Color:	Gris	Gris	Gris	Gris
Densidad.: (kg/mm³)	.00000142	.00000142	.00000142	.00000142
Dispersión.:	6%	6%	6%	6%
Ovalidad E/S.: (mm)	0.61	0.61	0.76	2.54
Espesor pared Min.: (mm)	2.03	2.54	3.18	3.80
Espesor pared Nom.: (mm)	2.09	2.62	3.28	3.92
Espesor pared Max.: (mm)	2.15	2.69	3.37	4.03
Longitud Min.: (mm)	5800	5800	5800	5800
Longitud Max.: (mm)	5820	5820	5820	5820
Ø interno Min. Exterior: (mm)	48.11	60.17	88.70	114.07
Ø interno Nom. Exterior: (mm)	48.26	60.32	88.90	114.80
Ø interno Max. Exterior: (mm)	48.41	60.47	89.10	115.53
Peso Min.: (Kg.)	2.42	3.79	7.04	10.84
Peso Nom.: (Kg.)	2.50	3.91	7.26	11.24
Peso Max.: (Kg.)	2.57	4.02	7.48	11.63
Empaque 1:(uds. x caja.)	10	1	1	1
Prueba de impacto (lb/ft):	150	190	220	220
Longitud de campana Min.:	54.80	69.15	82.55	101.60
Longitud de campana Max.:	54.80	69.15	82.55	101.60
Ovalamiento de Camp. Max.: (mm)	0.91	0.91	1.17	1.22
Ø Interno ent. Camp. Nom.: (mm)	48.56	60.63	89.31	114.76
Ø Interno ent. Camp. Min.: (mm)	48.41	60.48	89.11	114.53
Ø Interno ent. Camp. Max.: (mm)	48.71	60.78	89.51	114.99
Deflexión Bajo Carga (Rigidez):	350	450	450	525
Aplastamiento: (%)	70	70	70	70

Grabado:

Ø DE LA TUBERÍA RIGID PVC TYPE A UNDERGROUND ONLY-ENCASE IN CONCRETE PVC 1120 UL-651 (LOGO UL) / NORDOM 855 (sello) CORVI SONACA (LOGO CORVI) MADE IN DOMINICAN REPUBLIC /FECHA/HORA/MAQUINA NO. / HILERA NO.