

ESPECIFICACIÓN DE PRODUCTOS



TUBOS LISOS SCH40 -NSF

SONACA 
 Productos que resisten toda una vida

Tubos PVC	1/2"	3/4"	1"	1 1/4"
Norma:	ASTM D1785	ASTM D1785	ASTM D1785	ASTM D1785
Código:	340-0056	340-0081	340-0106	340-0131
Color:	Blanco	Blanco	Blanco	Blanco
Densidad.: (kg/mm³)	.00000142	.00000142	.00000142	.00000142
Dispersión.:	6%	6%	6%	6%
Ovalidad E/S.: (mm)	0.41	6.00	0.51	0.61
Espesor pared Min.: (mm)	2.77	2.87	3.38	3.56
Espesor pared Nom.: (mm)	2.86	2.96	3.48	3.67
Espesor pared Max.: (mm)	2.94	3.04	3.58	3.77
Longitud Min.: (mm)	5800	5800	5800	5800
Longitud Max.: (mm)	5820	5820	5820	5820
Ø interno Min. Exterior: (mm)	21.33	26.57	33.27	42.03
Ø interno Nom. Exterior: (mm)	21.39	26.67	33.40	42.16
Ø interno Max. Exterior: (mm)	21.44	26.77	33.53	42.29
Peso Min.: (Kg.)	1.33	1.76	2.61	3.54
Peso Nom.: (Kg.)	1.37	1.82	2.69	3.65
Peso Max.: (Kg.)	1.41	1.87	2.77	3.76
Empaque 1:(uds. x caja.)	25	20	10	10
Presión de trabajo: (psi)	600	480	450	370
Presión de ruptura: (psi)	1910	1540	1440	1180
Longitud de campana Min.:	36.00	40.00	40.00	58.00
Longitud de campana Max.:	42.00	50.00	50.00	65.00
Ovalamiento de Camp. Max.: (mm)	0.61	0.71	0.76	0.86
Ø Interno ent. Camp. Nom.: (mm)	21.54	26.87	33.65	42.42
Ø Interno ent. Camp. Min.: (mm)	21.44	26.77	33.52	42.29
Ø Interno ent. Camp. Max.: (mm)	21.64	26.97	33.78	42.55

Grabado:

TAMAÑO DE TUBO X LONGITUD PVC 1120 (D-7N) (600 PSI) @ 73°F (23°C) ASTM D1785 LOGO NDF/ CORVI SONACA (LOGO CORVI) MADE IN DOMINICAN REPUBLIC /FECHA/HORA/MAQUINA NO. / HILERA NO.

ESPECIFICACIÓN DE PRODUCTOS



TUBOS LISOS SCH40 -NSF

SONACA 
Productos que resisten toda una vida

Tubos PVC	1 1/2"	2"	3"	4"
Norma:	ASTM D1785	ASTM D1785	ASTM D1785	ASTM D1785
Código:	340-0156	340-0205	340-0305	340-0407
Color:	Blanco	Blanco	Blanco	Blanco
Densidad.: (kg/mm³)	.00000142	.00000142	.00000142	.00000142
Dispersión.:	6%	6%	6%	6%
Ovalidad E/S.: (mm)	0.51	0.61	0.76	2.50
Espesor pared Min.: (mm)	3.68	3.91	5.49	6.02
Espesor pared Nom.: (mm)	3.79	4.03	5.66	6.20
Espesor pared Max.: (mm)	3.90	4.14	5.82	6.38
Longitud Min.: (mm)	5800	5800	5800	5800
Longitud Max.: (mm)	5820	5820	5820	5820
Ø interno Min. Exterior: (mm)	48.11	60.17	88.70	114.07
Ø interno Nom. Exterior: (mm)	48.26	60.33	88.90	114.30
Ø interno Max. Exterior: (mm)	48.41	60.48	89.10	114.53
Peso Min.: (Kg.)	4.23	5.69	11.82	16.83
Peso Nom.: (Kg.)	4.36	5.87	12.18	17.34
Peso Max.: (Kg.)	4.49	6.04	12.54	17.85
Empaque 1:(uds. x caja.)	10	N/A	N/A	N/A
Presión de trabajo: (psi)	330	280	260	220
Presión de ruptura: (psi)	1060	890	840	710
Longitud de campana Min.:	58.00	58.00	97.00	120.00
Longitud de campana Max.:	65.00	65.00	112.00	130.00
Ovalamiento de Camp. Max.: (mm)	0.76	0.91	1.17	1.22
Ø Interno ent. Camp. Nom.: (mm)	33.65	60.63	89.31	114.76
Ø Interno ent. Camp. Min.: (mm)	33.52	60.48	89.11	114.53
Ø Interno ent. Camp. Max.: (mm)	33.78	60.78	89.51	114.99

Grabado:

TAMAÑO DE TUBO X LONGITUD PVC 1120 (D-7N) (600 PSI) @ 73°F (23°C) ASTM D1785 LOGO NDF/ CORVI SONACA (LOGO CORVI) MADE IN DOMINICAN REPUBLIC /FECHA/HORA/MAQUINA NO. / HILERA NO.

ESPECIFICACIÓN DE PRODUCTOS



TUBOS LISOS SCH40 -NSF

SONACA 
 Productos que resisten toda una vida

Tubos PVC	6"	8"	10"	12"
Norma:	ASTM D1785	ASTM D1785	ASTM D1785	ASTM D1785
Código:	340-0609	340-0806	340-1004	340-1205
Color:	Blanco	Blanco	Blanco	Blanco
Densidad.: (kg/mm³)	.00000142	.00000142	.00000142	.00000142
Dispersión.:	6%	6%	6%	6%
Ovalidad E/S.: (mm)	2.54	3.81	3.81	3.81
Espesor pared Min.: (mm)	7.11	8.18	9.27	10.31
Espesor pared Nom.: (mm)	7.33	8.43	9.55	10.62
Espesor pared Max.: (mm)	7.54	8.67	9.83	10.93
Longitud Min.: (mm)	5800	5800	5800	5800
Longitud Max.: (mm)	5820	5820	5820	5820
Ø interno Min. Exterior: (mm)	168.00	218.69	272.67	323.47
Ø interno Nom. Exterior: (mm)	168.28	219.08	273.05	323.85
Ø interno Max. Exterior: (mm)	168.56	219.46	273.43	324.23
Peso Min.: (Kg.)	29.60	44.55	63.18	83.54
Peso Nom.: (Kg.)	30.51	45.92	65.11	86.07
Peso Max.: (Kg.)	31.41	47.29	67.04	88.60
Empaque 1:(uds. x caja.)	N/A	N/A	N/A	N/A
Presión de trabajo: (psi)	180	160	140	130
Presión de ruptura: (psi)	560	500	450	420
Longitud de campana Min.:	150.00	160.00	190.00	220.00
Longitud de campana Max.:	160.00	170.00	220.00	240.00
Ovalamiento de Camp. Max.: (mm)	2.08	3.05	3.30	3.81
Ø Interno ent. Camp. Min.: (mm)	168.55	219.46	273.33	324.18
Ø Interno ent. Camp. Nom.: (mm)	168.83	219.84	273.71	324.56
Ø Interno ent. Camp. Max.: (mm)	169.11	220.22	274.09	324.94

Grabado:

TAMAÑO DE TUBO X LONGITUD PVC 1120 (D-7N) (600 PSI) @ 73°F (23°C) ASTM D1785 LOGO NDF/ CORVI SONACA (LOGO CORVI) MADE IN DOMINICAN REPUBLIC /FECHA/HORA/MAQUINA NO. / HILERA NO.