

# ESPECIFICACIÓN DE PRODUCTOS



## TUBOS LISOS SCH40 -19'

**SONACA**   
 Productos que resisten toda una vida

Tubos PVC	1/2"	3/4"	1"	1 1/4"
<b>Norma:</b>	ASTM D1785	ASTM D1785	ASTM D1785	ASTM D1785
<b>Código:</b>	340-0050	340-0075	340-0100	340-0125
<b>Color:</b>	Blanco	Blanco	Blanco	Blanco
<b>Densidad.: (kg/mm<sup>3</sup>)</b>	.00000142	.00000142	.00000142	.00000142
<b>Dispersión.:</b>	6%	6%	6%	6%
<b>Ovalidad E/S.: (mm)</b>	0.41	0.51	0.51	0.61
<b>Espesor pared Min.: (mm)</b>	2.77	2.87	3.38	3.56
<b>Espesor pared Nom.: (mm)</b>	2.86	2.96	3.48	3.67
<b>Espesor pared Max.: (mm)</b>	2.94	3.04	3.58	3.77
<b>Longitud Min.: (mm)</b>	5800	5800	5800	5800
<b>Longitud Max.: (mm)</b>	5820	5820	5820	5820
<b>Ø interno Min. Exterior: (mm)</b>	21.33	26.57	33.27	42.03
<b>Ø interno Nom. Exterior: (mm)</b>	21.39	26.67	33.40	42.16
<b>Ø interno Max. Exterior: (mm)</b>	21.44	26.77	33.53	42.29
<b>Peso Min.: (Kg.)</b>	1.33	1.76	2.61	3.54
<b>Peso Nom.: (Kg.)</b>	1.37	1.82	2.69	3.65
<b>Peso Max.: (Kg.)</b>	1.41	1.87	2.77	3.76
<b>Empaque 1:(uds. x caja.)</b>	25	20	10	10
<b>Presión de trabajo: (psi)</b>	600	480	450	370
<b>Presión de ruptura: (psi)</b>	1910	1540	1440	1180
<b>Longitud de campana Min.:</b>	25.40	31.75	38.10	44.45
<b>Longitud de campana Max.:</b>	25.40	31.75	38.10	44.45
<b>Ovalamiento de Camp. Max.: (mm)</b>	0.61	0.71	0.76	0.86
<b>Ø Interno ent. Camp. Nom.: (mm)</b>	21.54	26.87	33.65	42.42
<b>Ø Interno ent. Camp. Min.: (mm)</b>	21.44	26.77	33.52	42.29
<b>Ø Interno ent. Camp. Max.: (mm)</b>	21.64	26.97	33.78	42.55

### Grabado:

TAMAÑO DE TUBO X LONGITUD PVC 1120 PRESION SCH-40 (480 PSI) @ 73°F (23°C) ASTM D1785/NORDOM 855  
 CORVI SONACA (LOGO CORVI) MADE IN DOMINICAN REPUBLIC /FECHA/HORA/MAQUINA NO. / HILERA NO.

# ESPECIFICACIÓN DE PRODUCTOS



## TUBOS LISOS SCH40 -19'

**SONACA**   
 Productos que resisten toda una vida

Tubos PVC	1 1/2"	2"	3"	4"
<b>Norma:</b>	ASTM D1785	ASTM D1785	ASTM D1785	ASTM D1785
<b>Código:</b>	340-0150	340-0200	340-0300	340-0400
<b>Color:</b>	Blanco	Blanco	Blanco	Blanco
<b>Densidad.: (kg/mm<sup>3</sup>)</b>	.00000142	.00000142	.00000142	.00000142
<b>Dispersión.:</b>	6%	6%	6%	6%
<b>Ovalidad E/S.: (mm)</b>	0.61	0.61	0.76	2.54
<b>Espesor pared Min.: (mm)</b>	3.68	3.91	5.49	6.02
<b>Espesor pared Nom.: (mm)</b>	3.79	4.03	5.66	6.20
<b>Espesor pared Max.: (mm)</b>	3.90	4.14	5.82	6.38
<b>Longitud Min.: (mm)</b>	5800	5800	5800	5800
<b>Longitud Max.: (mm)</b>	5820	5820	5820	5820
<b>Ø interno Min. Exterior: (mm)</b>	48.11	60.17	88.70	114.07
<b>Ø interno Nom. Exterior: (mm)</b>	48.26	60.33	88.90	114.30
<b>Ø interno Max. Exterior: (mm)</b>	48.41	60.48	89.10	114.53
<b>Peso Min.: (Kg.)</b>	4.23	5.69	11.82	16.83
<b>Peso Nom.: (Kg.)</b>	4.36	5.87	12.18	17.34
<b>Peso Max.: (Kg.)</b>	4.49	6.04	12.54	17.85
<b>Empaque1:(uds. x caja.)</b>	10	N/A	N/A	N/A
<b>Presión de trabajo: (psi)</b>	330	280	260	220
<b>Presión de ruptura: (psi)</b>	1060	890	840	710
<b>Longitud de campana Min.:</b>	54.80	69.15	82.55	101.60
<b>Longitud de campana Max.:</b>	54.80	69.15	82.55	101.60
<b>Ovalamiento de Camp. Max.: (mm)</b>	0.91	0.91	1.17	1.22
<b>Ø Interno ent. Camp. Nom.: (mm)</b>	48.56	60.63	89.31	114.76
<b>Ø Interno ent. Camp. Min.: (mm)</b>	48.41	60.48	89.11	114.53
<b>Ø Interno ent. Camp. Max.: (mm)</b>	48.71	60.78	89.51	114.99

### Grabado:

TAMAÑO DE TUBO X LONGITUD PVC 1120 PRESION SCH-40 (480 PSI) @ 73°F (23°C) ASTM D1785/NORDOM 855  
 CORVI SONACA (LOGO CORVI) MADE IN DOMINICAN REPUBLIC /FECHA/HORA/MAQUINA NO. / HILERA NO.

# ESPECIFICACIÓN DE PRODUCTOS



## TUBOS LISOS SCH40 -19'

**SONACA**   
Productos que resisten toda una vida

Tubos PVC	6"	8"	10"	12"
<b>Norma:</b>	ASTM D1785	ASTM D1785	ASTM D1785	ASTM D1785
<b>Código:</b>	340-0600	340-0800	340-1000	340-1200
<b>Color:</b>	Blanco	Blanco	Blanco	Blanco
<b>Densidad.: (kg/mm<sup>3</sup>)</b>	.00000142	.00000142	.00000142	.00000142
<b>Dispersión.:</b>	6%	6%	6%	6%
<b>Ovalidad E/S.: (mm)</b>	2.54	3.81	3.81	3.81
<b>Espesor pared Min.: (mm)</b>	7.11	8.18	9.27	10.31
<b>Espesor pared Nom.: (mm)</b>	7.33	8.43	9.55	10.62
<b>Espesor pared Max.: (mm)</b>	7.54	8.67	9.83	10.93
<b>Longitud Min.: (mm)</b>	5800	5800	5800	5800
<b>Longitud Max.: (mm)</b>	5820	5820	5820	5820
<b>Ø interno Min. Exterior: (mm)</b>	168.00	218.69	272.67	323.47
<b>Ø interno Nom. Exterior: (mm)</b>	168.28	219.08	273.05	323.85
<b>Ø interno Max. Exterior: (mm)</b>	168.56	219.46	273.43	324.23
<b>Peso Min.: (Kg.)</b>	29.60	44.55	63.18	83.54
<b>Peso Nom.: (Kg.)</b>	30.51	45.92	65.11	86.07
<b>Peso Max.: (Kg.)</b>	31.41	47.29	67.04	88.60
<b>Empaque1:(uds. x caja.)</b>	N/A	N/A	N/A	N/A
<b>Presión de trabajo: (psi)</b>	180	160	140	130
<b>Presión de ruptura: (psi)</b>	560	500	450	420
<b>Longitud de campana Min.:</b>	165.40	20.45	190.50	228.90
<b>Longitud de campana Max.:</b>	165.40	152.40	190.50	228.90
<b>Ovalamiento de Camp. Max.: (mm)</b>	2.08	3.05	N/A	N/A
<b>Ø Interno ent. Camp. Nom.: (mm)</b>	168.83	219.84	273.33	324.18
<b>Ø Interno ent. Camp. Min.: (mm)</b>	168.55	219.46	273.33	324.18
<b>Ø Interno ent. Camp. Max.: (mm)</b>	169.11	220.22	274.09	324.94

### Grabado:

TAMAÑO DE TUBO X LONGITUD PVC 1120 PRESION SCH-40 (480 PSI) @ 73°F (23°C) ASTM D1785/NORDOM 855 CORVI SONACA (LOGO CORVI) MADE IN DOMINICAN REPUBLIC /FECHA/HORA/MAQUINA NO. / HILERA NO.